

**LANCASHIRE TESTING SERVICES LIMITED**

Lyon Road Industrial Estate : Kearsley : Bolton

Lancashire : BL4 8NB

Tel: +44 (0) 1204 792858

Email: enquiries@ltslab.co.uk

www.ltslab.co.uk

9630

TEST CERTIFICATE

CLIENT:	Agua Fabrics Ltd Hyde House The Hyde London NW9 6LH -	Certificate Number:	UK2000547 -1
		Date Received:	14/07/2020
		Date Issued:	20/07/2020
		Issue Number:	1
Contact:	Suzanne Ralton	Changes from previous issue (if applicable)	
Tel:	020820500050		
Email:	suzanne@aguafabrics.com		

SAMPLE IDENTIFICATION

Sample Name / Reference: Lavoro
Order / Batch No: 3020LAVO
Customer: -
Fabric Composition: 100% Polyester
Colour: -
Quality: -
Width: -

SPECIFICATION

BS7176:2007 + A1:2011 - Low Hazard

TEST METHOD

Flammability: BS EN 1021-1:2006 Part 1: Ignition source smouldering cigarette
BS EN 1021-2:2006 Part 2: Ignition source match flame equivalent
Pre-treatment: BS 5852:2006 Annex E - Water soaking procedure

Conclusion

The sample tested: **Complies** with the flammability requirements of:
BS 7176:2007 + A1:2011 Low hazard, taking into account uncertainty of measurement.
Comments: One Cigarette did not burn to completion

**LANCASHIRE TESTING SERVICES LIMITED**

Lyon Road Industrial Estate : Kearsley : Bolton

Lancashire : BL4 8NB

Tel: +44 (0) 1204 792858

Email: enquiries@ltslab.co.uk


www.ltslab.co.uk


9630

TEST CERTIFICATE**Test Results:-****BS7176:2007 + A1:2001 - Low Hazard - Specification for resistance to ignition of upholstered furniture for non-domestic seating by testing composites***"The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use."*

Sample Code		UK2000547 -1				
Sample Name / Reference		Lavoro				
Client		Agua Fabrics Ltd				
Date of test		20/07/2020				
Pre-Treatment		BS 5852:2006 Annex E - Water soaking procedure Line Dried during the day at ambient temperature				
Filling Type		Carpenter/RX36110 CMHR polyurethane foam of approximate density 36Kg/m3				
Size of test rig		Small: Back - 450 x 300 ± 2mm + Seat - 450 x 150 ± 2mm				
Test Conditions		Period h	Temperature °C	Relative humidity %	Air Flow m/s	Volume m ³
Conditioning of test specimens		≥16	23±2	50±5	-	-
Testing conditions		-	10-30	15-80	0.02-0.2	>20
Testing Source		Smouldering Cigarette Source				
Testing time limit		60 minutes after placement of smouldering cigarette.				
Test No.	Position	Ignition/ Non Ignition	Duration of: (min.sec)			Smouldering and flaming criteria exceeded: (If any)
			Ignition Source	Flames	Smoke	
1	RHS	NI	26.44	-	27.51	-
2	M	NI	13.11	-	30.08	-
2	LHS	NI	22.49	-	24.12	-
Testing Source		Match flame equivalent				
Testing time limit		2 minutes after removal of burner tube (120 seconds)				
Test No.	Position	Ignition/ Non Ignition	Duration of: (sec)			Smouldering and flaming criteria exceeded: (If any)
			Ignition Source	Flames	Smoke	
1	LHS	NI	15	15	29	-
2	M	NI	15	15	28	-
3	RHS	NI	15	15	30	-
RESULT:		SMOULDERING CIGARETTE SOURCE				PASS
		MATCH FLAME EQUIVALENT				PASS
KEY: I = Ignition, NI = Non Ignition, LHS = Left hand side, M = Middle, RHS = Right hand side						

On behalf of Lancashire Testing Services :

Tony Alcock,
Laboratory Technician:

 John Marsh,
Laboratory Technician:


 Peter Collings,
Operations Manager:
Issue Number: 1

Please note that copies of this original certificate are not valid