Lancashire Testing Services Ltd Units 26 & 27 Lyon Road Industrial Estate Kearsley BOLTON BL4 8NB



Test Report

Lab Ref number:	LTS1800098-5				
Date:	25/06/2018				
Sample submitted:	Kashmere				
Customer	Agua Fabrics				
Colour:	-				
Substrate:	Polyester				
Filling used:	Carpenter/RP21130 unmodified polyurethane foam of density 20-				
	22Kg/m³/Type B				
Test Required:	IMO 2010 FTP Code Part 8				
Gas Used:	Propane				
Cigarette Smoulder	11±4.0 min/50mm				
Time:					
Pre Treatment:	None				

Testing source			Smouldering Cigarette source						
Testin	g time limi	t	60 minutes after placement of smouldering cigarette						
Test	Position	Ignition/	Duration of: (min.sec)			Damage:			
No.		Non	Ignition	Flames	Smoke	Back:	Back:	Base:	Base:
		Ignition	source			Length	Width	Length	Width
1	RHS	NI	12.22	-	13.26	-	-	-	-
2	М	NI	12.45	-	13.55	-	-	-	-

Testing source			Butane Flame Ignition Source 1						
Testing time limit			2 minutes after removal of burner tube						
Test	Position	Ignition/	Duration of: (min.sec)			Damage: mm			
No.		Non	Ignition	Flames	Smoke	Back:	Back:	Base:	Base:
		Ignition	source			Length	Width	Length	Width
1	М	NI	20	25	40	-	-	-	-
2	RHS	NI	20	21	36	-	1	1	-
RESULT: SMOULDERING CIGARETTE SOURCE Non- Ignition									nition
BUTANE FLAME IGNITION SOURCE 1 Non -Ignition									
KEY: I = Ignition, NI = Non Ignition, LHS = Left hand side, M = Middle, RHS = Right hand side									

The results detailed relate only to the sample submitted and offer no guarantee for the batch or bulk of material produced. Please be advised that these results are only intended for advisory purposes as full test procedures may not have been used in their entirety.